

May 05 2016



Size: 2.063 in.
Wall: 0.156 in.
Weight: 3.25 lbs/ft
Grade: P110
Min. Wall Thickness: 87.5 %

Connection: Wedge 511™
Casing/Tubing: TUB



| PIPE BODY DATA | | | |
|----------------------------|-----------------------|----------------------------|----------------------|
| GEOMETRY | | | |
| Nominal OD | 2.063 in. | Nominal Weight | 3.25 lbs/ft |
| | | Standard Drift Diameter | 1.657 in. |
| Nominal ID | 1.751 in. | Wall Thickness | 0.156 in. |
| | | Special Drift Diameter | N/A |
| Plain End Weight | 3.18 lbs/ft | | |
| PERFORMANCE | | | |
| Body Yield Strength | 103 x 1000 lbs | Internal Yield | 14560 psi |
| | | SMYS | 110000 psi |
| Collapse | 14600 psi | | |
| WEDGE 511™ CONNECTION DATA | | | |
| GEOMETRY | | | |
| Connection OD | 2.126 in. | Connection ID | 1.686 in. |
| | | Make-Up Loss | 2.270 in. |
| Critical Section Area | 0.558 sq. in. | Threads per in. | 4.09 |
| PERFORMANCE | | | |
| Tension Efficiency | 59.7 % | Joint Yield Strength | 61 x 1000 lbs |
| | | Internal Pressure Capacity | 14560 psi |
| Compression Strength | 84 x 1000 lbs | Compression Efficiency | 81.6 % |
| | | Bending | 146 °/100 ft |
| External Pressure Capacity | 14600 psi | | |
| MAKE-UP TORQUES | | | |
| Minimum | 450 ft-lbs | Optimum | 500 ft-lbs |
| | | Maximum (*) | 800 ft-lbs |
| OPERATIONAL LIMIT TORQUES | | | |
| Operating Torque | 1400 ft-lbs | Yield Torque | 2100 ft-lbs |